

## XPO X-LED series

### Free Mounted

---




XPO X-LED Free Mounted can redefine your showcases, niches, exhibition areas or display areas.

It has a warm white light and high colour rendering. It has a black or aluminium coating. Other finishes are obtainable on request.

XPO X-LED offers multiple mounting options: suspended, wall-to-wall, free-standing and surface-mounted vertically or horizontally. As a minimum it requires 2 brackets for the mounting.

Its measurements are made to fit your specific needs.

- For indoor use / dry locations
- White light 3.000K
- External electronic driver
- Dimmable versions available
- Black or grey finish. (others on req.)
- Surface treatment, anodised



IP 20

0,7kg/m

±180°



Mounting clips



Material	Aluminium, plastic and other
Size W	Ø26 x min. 180 mm - max 1860 mm
Colour	Black and grey
Rotation	±150°
Total power consumption	24V DC
Driver mode	Constant voltage
Driver lifetime, expected	>50.000h
Supply voltage (mains)	100-240V 50-60Hz
LED power consumption	7.5W/m
LED efficacy	100 lm/W
LED lifetime, expected	>50.000h @Ta=25°C
Fixture luminous flux	720 lm/m
Dimmer systems applicable	1-10V, PUSH (mains)
Cooling system	Natural convection
Ambient temperature	-20° to 45°C Max
Lumen maintenance	L70 B0 after 50.000h
Applied LED	Xicato
CCT (nominal)	3000K, other CCT on request
CRI-8 (Ra) typical value	Min. 98
Transmission through cover	53%, 80%, 93%
Cleaning	Dry cloth or air

Item no.

XPO X-LED Free Mounted black	1207 0510
XPO X-LED Free Mounted grey	1207 0520

# RobLight

RobLight A/S, Nordhavnsvej 1A, DK-9900 Frederikshavn, T: +45 9244 4888, E: info@rob-light.com, www.rob-light.com

RobLight accepts no responsibility for possible errors in catalogues, brochures and other printed material.  
RobLight reserves the right to alter or discontinue its products without notice. © 2019 RobLight A/S