

Essential 3SL Clear



Essential 3SL Clear. For indoor and damp locations. For display, decorative and task lighting. For lighting objects and surfaces. For showcases, niches, shelves, walls and many other applications. Multiple colour temperatures. Surface-mounted or recessed. Fixed or adjustable. Single or double LED row. Opal models available.

From the Essential series. Consistent, uniform light. Excellent light output. High CRI. Nichia LED technology. Easy to install. Easy to move. Easy to reuse. Hard-working, high-quality, low-energy light in tiny multipurpose conduits. LED lighting made simple.

Essential 3SL Clear


For indoor use/damp locations
 Single or double LED row
 Recessed or surface-mounted
 Adjustable or fixed mounting clips
 Conduit min. 120 mm, max. 2.42 m
 16 mm between LEDs
 Default wire length 2.44 m
 Anodised aluminium
 Clear acrylic cover
 Opal models also available
 Operating ambient temperature -30° to +40°
 2,700 K, 3,000 K, 3,500 K, 4,000 K or 4,500 K
 Beam angle 112°
 Dimmable
 Constant Voltage 24 V
 Nichia LED technology
 CRI (Ra) 85
 Five-year warranty
 LED standard lifetime 50,000 hours



Essential 3SL Clear Single

Fixture luminous flux 1045 to 1283 lm/m
 Fixture luminous efficacy 58 to 71 lm/W
 Single row of LEDs
 18 watt

18W per m conduit **IP 64** **0.85 kg** per m conduit




	Item no.		Item no.		
Black	2,700 K	1994 0112	Grey	2,700 K	1994 0012
	3,000 K	1994 0113		3,000 K	1994 0013
	3,500 K	1994 0114		3,500 K	1994 0014
	4,000 K	1994 0115		4,000 K	1994 0015
	4,500 K	1994 0116		4,500 K	1994 0016

Essential 3SL Clear Double

Fixture luminous flux 1296 to 1591 lm/m
 Fixture luminous efficacy 36 to 44 lm/W
 Double row of LEDs
 36 watt

36W per m conduit **IP 64** **0.85 kg** per m conduit



	Item no.		Item no.		
Black	2,700 K	1995 0112	Grey	2,700 K	1995 0012
	3,000 K	1995 0113		3,000 K	1995 0013
	3,500 K	1995 0114		3,500 K	1995 0014
	4,000 K	1995 0115		4,000 K	1995 0015
	4,500 K	1995 0116		4,500 K	1995 0016